

X5 FastMig Auto

TECHNICAL SPECIFICATIONS

X5 FastMig Auto	X5 Power Source 400		X5 Power Source 500		X5 Wire Feeder 300 AP	X5 Wire Feeder 300 APC	X5 Wire Feeder HD300 AP	X5 Wire Feeder HD300 APC	X5 Cooler	
	Power Source 400	WP	Power Source 500	WP						
Product code					X5240300000	X5250300000	X5270300000	X5280300000	X5600000000	
Connection voltage 3~ 50/ 60 Hz	380...460 V ±10 %	380...460 V ±10 %	380...460 V ±10 %	380...460 V ±10 %						
Output 60% ED	400 A	400 A	500 A	500 A						
Output 100% ED	350 A	350 A	430 A	430 A						
Wire feed mechanism					4-roll, single-motor	4-roll, single-motor	4-roll, single-motor	4-roll, single-motor		
Rated cooling power at 1 l/ min									1.1 kW	
Recommended coolant									MGP 4456 (Kemppi mixture)	
Gun connection					Euro	Euro	Euro	Euro		
Filler wires					Fe 0.8 ... 2.0 mm Ss 0.8 ... 2.0 mm Mc/ Fc 0.8 ... 2.4 mm Al 0.8 ... 2.4 mm	Fe 0.8 ... 2.0 mm Ss 0.8 ... 2.0 mm Mc/ Fc 0.8 ... 2.4 mm Al 0.8 ... 2.4 mm	Fe 0.8 ... 2.0 mm Ss 0.8 ... 2.0 mm Mc/ Fc 0.8 ... 2.4 mm Al 0.8 ... 2.4 mm	Fe 0.8 ... 2.0 mm Ss 0.8 ... 2.0 mm Mc/ Fc 0.8 ... 2.4 mm Al 0.8 ... 2.4 mm		
Wire feed speed					0.5 ... 25 m/ min	0.5 ... 25 m/ min	0.5 ... 25 m/ min	0.5 ... 25 m/ min		
Diameter of feed rolls					32 mm	32 mm	32 mm	32 mm		
Welding current and voltage range, MIG	15 A/12 V ... 400 A/42 V	15 A/12 V ... 400 A/42 V	15 A/10 V ... 500 A/47 V	15 A/10 V ... 500 A/47 V						
Welding current and voltage range, TIG	15 A/1 V ... 400 A/42 V	15 A/1 V ... 400 A/42 V	15 A/1 V ... 500 A/47 V	15 A/1 V ... 500 A/47 V						
Welding current and voltage range, MMA	15 A/10 V ... 400 A/42 V	15 A/10 V ... 400 A/42 V	15 A/10 V ... 500 A/47 V	15 A/10 V ... 500 A/47 V						
Operating temperature range	-20...+40 °C	-20...+40 °C	-20...+40 °C	-20...+40 °C	-20...+40 °C	-20...+40 °C	-20...+40 °C	-20...+40 °C	-20...+40 °C	

X5 FastMig Auto	X5 Power Source 400	X5 Power Source 400 WP	X5 Power Source 500	X5 Power Source 500 WP	X5 Wire Feeder 300 AP	X5 Wire Feeder 300 APC	X5 Wire Feeder HD300 AP	X5 Wire Feeder HD300 APC	X5 Cooler
External dimensions LxWxH	750 x 263 x 456 mm	750 x 263 x 456 mm	750 x 263 x 456 mm	750 x 263 x 456 mm	650 x 230 x 410 mm	650 x 230 x 410 mm	670 x 240 x 465 mm	670 x 240 x 465 mm	
Weight (no accessories)	39.0 kg	39.0 kg	39.5 kg	39.5 kg	10.9 kg	10.9 kg	14.4 kg	14.4 kg	14.3 kg
Degree of protection	IP23S	IP23S	IP23S	IP23S	IP23S	IP23S	IP23S	IP23S	
Wire spool weight, max.					20 kg	20 kg	20 kg	20 kg	
Wire spool diameter, max.					300 mm	300 mm	300 mm	300 mm	
Tank volume									4 l
EMC class	A	A	A	A	A	A	A	A	
Storage temperature range	-40...+60 °C	-40...+60 °C	-40...+60 °C	-40...+60 °C	-40...+60 °C	-40...+60 °C	-40...+60 °C	-40...+60 °C	-40...+60 °C
Additional information		Includes WiseSteel and WiseFusion special process and X5 Work Pack 1-MIG with 32 welding programs.		Includes WiseSteel and WiseFusion special process and X5 Work Pack 1-MIG with 32 welding programs.					
Shielding gas pressure (max)					0.5 MPa	0.5 MPa	0.5 MPa	0.5 MPa	
Operating temperature range (with recommended coolant)									-10...+40 °C
Degree of protection (when mounted)									IP23S
Welding current, 60 %					500 A	500 A	500 A	500 A	
Welding current, 100 %					430 A	430 A	430 A	430 A	